



- Up to now, if we want to store an arbitrary amount of data, we must use an array
 - We can create a structure with a fixed number of member variables, but we can't change that amount
- · Recall that arrays occupy a block of memory
 - The memory is either allocated
 - · Statically by the compiler on the stack, or
 - · Dynamically by the operating system on the heap
 - In either case, you cannot go back and change the allocated memory



- · In this lesson, we will:
 - Review that arrays can be great under certain circumstances
 - See that there are significant weaknesses
 - Fixed size
 - · Expensive to move many entries
 - · Same type
 - Understand that there must be other appraoches



- · Arrays can be blindingly fast:
 - Accessing or changing an entry is very fast
 - · Sometimes called random access
 - If it is sorted, we can search it quickly

1



• Suppose you have an array with capacity 20, but it is currently storing 10 pieces of information:

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
18	20	19	21	21	22	21	23	22	24										

 Next, suppose a new datum comes along that must be placed first, say 17:

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
17	18	20	19	21	21	22	21	23	22	24									

- This required us copy all ten entries over by one

⊚090 ECE150 ₩



- · Increasing any of these has cascading effects:
 - Increasing the weight may either:
 - Decrease portability
 - · Increase weight-bearing structures
 - Increasing cost will decrease competitive advantages or decrease profits
 - Increasing power consumption may either:
 - · Decrease battery life
 - · Increase the battery size
 - This further increases the weight
 - Increasing heat may either:
 - · Require a larger heat sink and cooling apparatus
 - Thus further increasing the weight
 - · Decrease lifetime



- Another issue is: suppose you normally only need to store on the order of 10 items, but in the worst case, you may have to store hundreds of items of data
 - Is it not a waste of memory to perpetually store a sufficiently large array that may be used a few minutes a day
- This is not an issue with larger general-purpose computing where memory is cheap, but consider an embedded system
 - Additional memory costs includes an increase in
 - · weight
 - · cost
 - · power consumption
 - heat

9000 ECE150



- · This is also an issue with operating systems
 - There are many queues were, for example, an executing program is waiting
 - · To use the printer
 - · For additional memory
 - · For input
- Most of these queues are empty or perhaps with one or two executing programs waiting some service
 - Unfortunately, the operating system must always be ready for an arbitrary number of executing programs waiting for some service...
 - Do we have an array of size 1024 for each such service?
 - · How about 2048?



· Suppose we have two arrays, and we want to concatenate them:

0									9	10	11	12	13	14	15	16	17	18	19
27	39	82	84	57	82														
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
34	27	29	39	12	29	59	23												

- Not a problem: copy the entries from the second to the first
- Still slow if the second array is large

0000 ECE150



- · Suppose we have a string which we are editing:
 - "A Elbereth Gilthoniel silivren penna míriel o menel aglar elenath! Na-chaered palan-díriel o galadhremmin ennorath, Fanuilos, le linnathon nef aear, sí nef aearon!"
- · Strings are by default stored as arrays
 - How much work is required to edit an array?

90 ECEIL



· What do we do here?

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
27	39	82	84	57	82	58	48	27	37	85	94	23	75	23	85				
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
34	27	29	39	12	29	59	23	91	98	75	82	66	42						

- What must we do now?
- This will be even more expensive...why?

©000 ECELLO



· Similarly, in your IDE, you are editing your code:

```
recorded to the control of the contr
```

3



- All the arrays we have looked at so far also have one important weakness:
 - All primitive arrays must be of the same type
 - At the very least, all entries must occupy the same amount of memory



- · Following this lesson, you now
 - Understand there are weaknesses in arrays
 - · They cannot effectively be used in all situations
 - Know that the characteristics of arrays are sometimes weaknesses
 - Understand that we need a different approach to storing arbitrary amounts of information

ECEI 50 P



[1] No references?

Issues with arrays

Colophon

These slides were prepared using the Georgia typeface. Mathematical equations use Times New Roman, and source code is presented using Consolas.

The photographs of lilacs in bloom appearing on the title slide and accenting the top of each other slide were taken at the Royal Botanical Gardens on May 27, 2018 by Douglas Wilhelm Harder. Please see

https://www.rbg.ca/

for more information.







DOGO ECEL

1



These slides are provided for the ECE 150 Fundamentals of Programming course taught at the University of Waterloo. The material in it reflects the authors' best judgment in light of the information available to them at the time of preparation. Any reliance on these course slides by any party for any other purpose are the responsibility of such parties. The authors accept no responsibility for damages, if any, suffered by any party as a result of decisions made or actions based on these course slides for any other purpose than that for which it was intended.

9000 EGE170