

_



- Please remember, we don't expect you know how to implement a graphical user interface
 - This is the result of years of experience and a team of software engineers and developers working together
- We are presenting this as an example of where inheritance could be useful in the real world
 - Try to understand why we are suggesting and describing



00 0 3 0

3



- · In this lesson, we will:
 - Describe another application of inheritance
 - See the need for a common class that contains shared information
 - Describe subsequent benefits of such an approach
 - Describe how to declare a class as abstract

EGEN

<u>00</u>030

2



- A graphical user interface window can either be a frame or a dialog
 - A frame has:
 - · A title bar with an icon, text, and color
 - · Possibly a menu bar
 - · Possibly a tool bar
 - Content
 - A dialog has:
 - · A title bar with text
 - Content





@ **(196**)

A windows class for graphical user interfaces Graphical user interface

- Each of these has information that must be stored in order to correctly display it
 - Thus, we would have two separate classes: class Frame; class Dialog;

0000

5



A windows class for graphical user interfaces An example of displaying a frame

Here is a possible minimal application using a frame:

```
int main() {
    Frame main_frame{};
    main_frame.title_text( "Hello world!" );
    main_frame.title_background_color( RGB_color{ 93, 102, 21 } );
    main_frame.title_text_color( RGB_color{ 255, 255, 255 } );
    main_frame.title_icon( "image.png" );
    // No menu bar unless one is added
    // No tool bar unless one is added
    main_frame.display();
    return 0;
}
```

7





· A constructor takes a number of arguments,

but too many will overwhelm the user leading to errors:

```
Frame main_frame{ "Hello world",
   Font{ "Times New Roman", 16 },
   "my_icon.png",
   100, 70, 593, 231,
   RGB_Color{ 15, 25, 193 },
   RGB_Color{ 255, 255 },
   true, false, false, true, 10, 10 };
```

 Consequently, many parameters automatically have default values that can only be set via member functions

@ <u>000</u>







• Here is a minimal implementation of a dialog:

```
int main() {
    Dialog query{};
    query.title_text( "Question" );
    query.title_background_color( RGB_color{ 93, 102, 21 } );
    query.title_text_color( RGB_color{ 255, 255, 255 } );

    Return_type value{ query.display() };
    return 0;
}
```





(a) (1) (b) (c)

A windows class for graphical user interfaces of Is one derived from the other?

- · There are significant differences between frames and dialogs
 - Dialogs are modal and have return values
 - Frames have menu bars and tool bars





- · However, there are some features that are in common
 - The title bar background color, text and text color
 - The member functions used to set these
 - The display member function

(C) (130)

ECENSO

9

11

A windows class for graphical user interfaces 11 Common features

· Compare these two classes:


```
class Window {
                               public:
                               private:
                           };
class Frame { public Window {
                                                    class Dialog { public Window {
       Return_type display();
                                                            Return_type display();
       // Other common member functions
                                                            // Other common member functions
       // Other member functions
                                                            // Other member functions
   private:
                   title_bar_icon_;
                                                            RGB_color title_bar_background_color_;
       RGB_color title_bar_background_color_;
                                                            std::string title_bar_text_;
       std::string title_bar_text_;
       Menu bar
                   menu bar :
                                                    };
       Tool har
                   tool_bar_
       Panel
                   content_;
```

A windows class for graphical user interfaces **Common features** class Frame { public: Return_type display(); // Other common member functions // Other member functions private: Image title_bar_icon_; RGB_color title_bar_background_color_; std::string title_bar_text_; RGB_color title_bar_text_color; Menu bar menu bar ; Tool bar tool bar ; Panel content_; }; class Dialog { public: Return type display(); // Other common member functions // Other member functions private: RGB_color title_bar_background_color_ std::string title_bar_text_; RGB color title bar text color Panel content_; };

10



· Thus, our class diagram would be as follow:



 In a next topic, we will describe how we can use inheritance to display the content of both frames and dialogs

@ **(196**)

ECHINO V



- · One great benefit of inheritance is uniformity:
 - Suppose with your next release, you include additional features:
 - · A title text typeface
 - Helvetica, Georgia, Cambria, etc.
 - · A title text style
 - Italicized
 - · A title text weight
 - Bold
 - · A title text size
 - Without a common base class, you would implement all these features in each class separately
 - You may forget, or may not have sufficient time to do both
 - · This will annoy users
 - Doing it once in the base class includes these changes in both derived classes



13

<u>@ 000</u>



- · Following this lesson, you now
 - Have seen another application of inheritance
 - Understand the benefit of creating a common base class
 - Discussed abstract classes that cannot be declared in a program



- · Can we declare an instance of a window?
 - There is no point in declaring an instance of a window class, as the window class cannot be displayed
 - We can assign the display() function the value 0
 - · This declares this class as being an abstract class
 - · That is, it is an idea,

and not something that can be concretely implemented

 Derived classes must implement their versions of this member function to allow users to declare instances of these classes

```
class Window {
    public:
        Return_type display() = 0;
        // Other common member functions
    private:
        // Common member variables
    };
```



14



- [1] https://en.wikipedia.org/wiki/Linked_list
- [2] https://en.wikipedia.org/wiki/Node_(computer_science)



@ O O O

16

(C) (190)

15

A windows class for graphical user interfaces 17

These slides were prepared using the Georgia typeface. Mathematical equations use Times New Roman, and source code is presented using Consolas.

The photographs of lilacs in bloom appearing on the title slide and accenting the top of each other slide were taken at the Royal Botanical Gardens on May 27, 2018 by Douglas Wilhelm Harder. Please see

for more information.







A windows class for graphical user interfaces 18

These slides are provided for the ECE 150 Fundamentals of Programming course taught at the University of Waterloo. The material in it reflects the authors' best judgment in light of the information available to them at the time of preparation. Any reliance on these course slides by any party for any other purpose are the responsibility of such parties. The authors accept no responsibility for damages, if any, suffered by any party as a result of decisions made or actions based on these course slides for any other purpose than that for which it was intended.

0000

18

